

## Tender text

### BQ-CC55

#### Plug-in quick charger,

from PANASONIC.

- For 1-4 NiMH eneloop rech. batteries, AA size or AAA size
- Charging control for each slot
- Microprocessor-controlled charging control (- $\Delta$ U method)
- Safety timer
- Reverse polarity protection, temperature monitoring
- Detection of faulty battery
- LED status indication for each charging slot

Specifications:

Category	plug-in quick charger
Input voltage	~ 100-240 V/50-60 Hz/300 mA
Output voltage	4 x DC 1.5 V
Charging/output current	3.2 A (rech. batt. AA size) 1.2 A (rech. batt. AAA size)
Charging time	dep. on capacity, size and number: from 0.75 h on
Trickle charge	yes
Connections	4 x battery compartment
Overheat protection	yes
Reverse polarity protection	yes
Detection of faulty battery	yes
Admiss. ambient temp.	0-35 °C
Dimensions	86 x 76 x 120 mm
Weight	124 g
Other features	- $\Delta$ V method, safety timer, charging control for each slot

Brand: PANASONIC

Type: BQ-CC55

Quantity: 1

Packing dimensions (W x H x L): 0.105 x 0.07 x 0.2 m

Gross weight: 0.18 kg

Net weight: 0.124 kg

Item weight (w/o accessories): 0.124 kg