

Components

Energy, Measuring and DIY

PSLF-12/12

Order No. 27.2120

PSLF-20/12

Order No. 27.1230

LED switch-mode power supplies, slimline design, for indoor applications.

- Especially for LED installations
- Low-noise according to EMC standard EN 61000-3-2 class A
- Protected against short circuit, overload, overvoltage
- Connection via screw terminals
- Plastic housing with mounting flange

Model	PSLF-12/12	PSLF-20/12
Input voltage	~ 230 V/50 Hz	~ 230 V/50 Hz
Output voltage	= 12 V	= 12 V
Charging/output current	1 A	1.67 A
Admiss. ambient temp.	-20+50 °C	-20+45 °C
Dimensions	128 x 13 x 50 mm	128 x 13 x 50 mm
Weight	67 g	70 g



PS-100/12S

Order No. 27.3500

PS-100/24S

Order No. 27.3510

Built-in power supplies

- Protected against short circuit, overload and overvoltage
- Fine adjustment of output voltage
- Aluminium housing
- Mains connection and low-voltage connection via screw terminals

Model	PS-100/12S	PS-100/24S
Input voltage	~ 100-240 V	~ 100-240 V
Output voltage	= 12 V	= 24 V
Charging/output current	8.5 A	4.5 A
Admiss. ambient temp.	-30+70 °C	-30+70 °C
Dimensions	97 x 30 x 129 mm	97 x 30 x 129 mm
Weight	0.314 kg	0.305 kg



PS-200/12S

Order No. 27.3520

PS-200/24S

Order No. 27.3530

Built-in power supplies

- Protected against short circuit, overload and overvoltage
- Fine adjustment of output voltage
- Aluminium housing
- Mains connection and low-voltage connection via screw terminals

Model	PS-200/12S	PS-200/24S
Input voltage	~ 100-240 V	~ 100-240 V
Output voltage	= 12 V	= 24 V
Charging/output current	16.7 A	8.4 A
Admiss. ambient temp.	-30+70 °C	-30+70 °C
Dimensions	115 x 30 x 215 mm	115 x 30 x 215 mm
Weight	0.718 kg	0.725 kg



PS-320/12S

Order No. 27.3540

PS-320/24S

Order No. 27.3550

Built-in power supplies

- Protected against short circuit, overload and overvoltage
- Fine adjustment of output voltage
- Aluminium housing
- Mains connection and low-voltage connection via screw terminals

Model	PS-320/12S	PS-320/24S
Input voltage	~ 100-240 V	~ 100-240 V
Output voltage	= 12 V	= 24 V
Charging/output current	26.7 A	13.4 A
Admiss. ambient temp.	-30+70 °C	-30+70 °C
Dimensions	115 x 30 x 215 mm	115 x 30 x 215 mm
Weight	0.824 kg	0.824 kg

