

# Components

## Energy, Measuring and DIY

### TL-250

Order No. 07.0360



#### Pair of test leads

- Highly flexible PVC test lead, red/black
- 4 mm right-angle safety plug
- 2 mm test prod
- Test lead Ø 3 mm, CAT III 1,000 V 10 A
- Length: 120 cm




### TH-40

Order No. 07.0160



#### Pair of clamp-type test prods 5 A, for pushing onto the safety test leads of the TLP-... series.

- Colour: red and black
- Flexible shaft
- Telescopic spring wire hooks
- According to CAT II (1,000 V)
- All-insulated due to covered plug-in contacts, Ø 4 mm
- Total length: 160 mm



### CC-320

Order No. 07.0080

#### Combo test lead set

- Various adapters
- Cable length: 90 cm



### TH-1/RT

Order No. 07.0180

### TH-1/SW

Order No. 07.0190

#### Miniature clamp-type test prods

- For small objects like IC connectors
- Test lead can be soldered on after removing the cap



- Red (RT) or black (SW)

### CC-311A

Order No. 07.0030



#### Test leads

- Black and red
- Highly flexible
- 2 mm plugs and banana plugs
- Length: 100 cm



### TH-10/RT

Order No. 07.0200

### TH-10/SW

Order No. 07.0210

#### Subminiature clamp-type test prods

- High precision
- Special miniature design for hard-to-reach measuring points



- Length: 40 mm
- Red (RT) or black (SW)

### TLP-100/RT


Order No. 07.0730

### TLP-100/SW

Order No. 07.0740

#### Test Leads

- With spliced, stackable banana plugs
- Highly flexible cable with PVC insulation
- Suitable for signal voltages and safety extra-low voltages (SELV)



- Length: 100 cm
- Red (RT) or black (SW)

### KH-15

Order No. 03.0380

#### Multi-purpose cable holder, for accessibly storing all kinds of cables and test leads.

- With 16 slots of different widths
- Dimensions: 325 x 90 mm



### CC-313

Order No. 07.0050



#### Test leads

- Banana plugs and alligator clips
- Length: approx. 100 cm



### DMT-4CC

Order No. 07.0640

#### Soft carrying bag, for digital and analogue multimeters.

- Soft imitation leather
- With wrist strap and inner lining
- Inside dimensions: 110 x 190 x 50 mm




### MK-612S

Order No. 07.0120



#### Connection leads

- Two leads each in the colours red, black, green, yellow, white
- Insulated alligator clips
- Length: 45 cm



### VD-100

Order No. 29.1990

#### Non-contact voltage tester

- Induction detector for voltages of ~ 100-600 V/50-60 Hz
- Audible and visible warning
- CAT III 1,000 V
- Power supply via 2 x 1.5 V batteries AAA size (not supplied)

