

Alarm Units

SAG-22

Order No. 04.1870



Alarm unit, with strobe light system in LED technology.

- Visual and audible signalling device
- Impact-proof plastic housing with cover contact and tear-off wall cable
- Siren activation PCB and flashlight PCB are moisture-proof due to special coating
- Electronic siren
- Suitable for indoor and outdoor applications
- Admissible ambient temperature: -20 °C to +70 °C
- Operating voltage: = 12 V

Model	SAG-22
Description	alarm unit
Flash energy	2 Ws
Sensitivity	100 dB
Operating voltage	= 12 V
Current consumption	120 mA (siren) 20 mA (flash)
Power supply	= 12 V/120 mA (siren) = 12 V/20 mA (flash)
Housing	plastic
Protective class	IP54
Dimensions	190 x 270 x 85 mm
Admiss. ambient temp.	-20 to +70 °C
Weight	717 g



SAG-32

Order No. 04.1170



Alarm unit, with strobe light system in LED technology.

- Visual and audible signalling device
- Aluminium housing with tamper switch
- Electronic siren
- Suitable for indoor and outdoor applications
- Admissible ambient temperature: -10 °C to +50 °C
- Operating voltage: = 12 V

Model	SAG-32
Description	alarm unit
Flash energy	2 Ws
Sensitivity	> 100 dBA
Operating voltage	= 12 V
Current consumption	320 mA (siren) 100 mA (flash), 70 mA (flash rotation)
Power supply	= 12 V/320 mA (siren) = 12 V/100 mA (flash), = 12 V/70 mA (flash rotation)
Housing	aluminium
Protective class	IP54
Dimensions	190 x 352 x 155 mm
Admiss. ambient temp.	-10 to +50 °C
Weight	1,665 g



SAG-42

Order No. 04.3090



Alarm unit, with strobe light system.

- Visual and audible signalling device
- Impact-proof and UV-resistant polycarbonate housing with tamper switch
- Piezo siren
- Suitable for indoor and outdoor applications
- Admissible ambient temperature: -10 °C to +50 °C
- Operating voltage: = 12 V

Model	SAG-42
Description	alarm unit
Flash energy	2.5 Ws
Sensitivity	> 100 dB
Current consumption	= 12 V/370 mA (siren) = 12 V/200 mA (flash)
Housing	UV-resistant polycarbonate
Protective class	IP34
Dimensions	110 x 260 x 65 mm
Admiss. ambient temp.	-10 to +50 °C
Weight	508 g



SAG-100

Order No. 04.3960



Alarm unit, with strobe light system in LED technology.

- Visual and audible signal device, can be controlled individually
- 4 LEDs
- Piezo siren
- Operating voltage: = 12 V
- Connection cable: 25 cm

Model	SAG-100
Description	alarm unit
Flash energy	-
Sensitivity	95 dB/W/m
Operating voltage	= 12 V
Current consumption	200 mA (siren + flash) 90 mA (flash only)
Power supply	12 V/200 mA (siren + flash) 12 V/90 mA (flash only)
Housing	ABS plastic
Dimensions	74 x 122 x 46 mm
Admiss. ambient temp.	0-40 °C
Weight	112 g

